

RECEIVED
CENTRAL FAX CENTER
SEP 05 2006

IN THE CLAIMS:

1. (Cancelled)

2. (Currently Amended) A medical instrument system using a diathermic snare and an endoscope in combination with each other, the endoscope including an inserting section [[having]] which is to be inserted into a body cavity, and includes a distal end and a proximal end, and a cylindrical cap section mounted on the distal end of the inserting section, the cap section having a distal end, [[and]] a proximal end and an engagement projection,

wherein the ~~cap section includes an~~ engagement projection includes a bent portion which is ~~bendable~~ bent inward at the distal end of the cap section; [[and]]

wherein the diathermic snare comprises:

~~a loop section which is connected to a distal end of an operating wire, which is insertable into an elongated flexible sheath having a distal end and a proximal end, and which is allowed to be looped, the loop section being looped while being projected from the distal end of the sheath when the operation wire is pushed forward toward the distal end of the sheath and being inserted into the sheath when the operation wire is pulled toward the proximal end of the sheath; and~~

a flexible sheath having a distal end and a proximal end;

an operation wire inserted into the flexible sheath to be movable forwards and backwards, and having a distal and a proximal end;

a snare wire coupled to the distal end of the operation wire, and including a loop section which expands to loop;

an operating section coupled to the proximal end of the flexible sheath, the operating section including a guide member and a slider, the guide member, extending in an

axial direction of the flexible sheath, the slider being movable forwards and backwards in the axial direction of the flexible sheath, and coupled to the proximal end of the operating wire;
and

a distal-end ~~[[bending]]~~ bent portion provided at the distal end of the loop section, ~~the bending portion being bendable and bent~~ in a direction that intersects a plane formed by the loop section, and conforming to a corner of a bending portion of the engagement projection when the loop section expands along the inner circumference of the projection;

wherein the slider is moved forwards along the guide member, loop section of the snare wire is projected from the distal end of the sheath, the snare wire expands to loop, and the loop section expands along the inner circumference surface of the engagement portion, and when the slider is moved backwards along the guide member, the loop section of the snare wire is retreated into the sheath; and

wherein the loop section expands along the inner circumference of the projection, the distal-end bent portion conforms to a corner of the bent portion of the engagement projection, and extends along an inner circumferential wall of the distal end of the cap section.

3. (Original) The medical instrument system according to claim 2, wherein the cap section has a main body that is made of transparent materials.

4. (Original) The medical instrument system according to claim 2, wherein the engagement projection has a flange-shaped engagement projection that projects toward an inner surface of the cap section in proximity to a leading edge of the cap section.

5. (Original) The medical instrument system according to claim 2, wherein:
the cap section has a fixing section at the proximal end thereof, the fixing
section being fixed to a distal end of the endoscope; and

the medical instrument system further comprises a soft tube having an open
distal end and an open proximal end, the soft tube being arranged alongside the inserting
section of the endoscope when the fixing section is fixed to the distal end of the endoscope,
and the open distal end communicating with an inside of the cap section.

6. (Original) The medical instrument system according to claim 2, wherein the
bending portion of the loop section bends at a bend angle which is almost perpendicular to the
plane formed by the loop section.

7. (Original) The medical instrument system according to claim 2, wherein the
bending portion of the loop section bends at an acute bend angle corresponding to an acute
angle to the plane formed by the loop section.

8. (Original) The medical instrument system according to claim 2, wherein:
the cap section has an inclined plane corresponding to a plane of the distal end
of the cap section which is inclined to the axial direction of the sheath; and
the bending portion of the loop section bends in the axial direction of the
sheath.

9. (Original) The medical instrument system according to claim 8, wherein the
plane formed by the loop section has an inclination angle that is set such that the plane is
almost parallel to the inclined plane of the cap section.

10. (Original) The medical instrument system according to claim 8, wherein:
the inclined plane of the cap section inclines at an acute angle in the axial
direction of the sheath; and
the bending portion of the loop section bends at a bend angle that is equal to an
inclination angle of the inclined plane.

11. (Original) The medical instrument system according to claim 2, wherein
the loop section has a diameter that is equal to an inside diameter of the cap section.

12. (Original) The medical instrument system according to claim 2, wherein
the loop section rotates around an axis of the sheath.

13. (Previously Presented) A method of assembling a medical instrument
system using a diathermic snare and an endoscope in combination with each other, the method
comprising:

a diathermic snare inserting step of mounting a cylindrical cap section on a
distal end of an inserting section of the endoscope, and projecting a distal end of a sheath of
the diathermic snare forward from the cap section;

a loop section projecting step of projecting the loop section from the sheath
while the distal end of the sheath is projected from the cap section;

a loop section direction adjusting step of rotating the loop section around an
axis of the sheath when necessary and adjusting a direction of the loop section;

a retracting step of retracting the loop section into the cap section;

a cap section pressing step of pressing a leading edge of the cap section against
an object; and

a loop section setting step of pushing the sheath to bring the loop section into tight contact with the engagement projection and expanding the loop section circularly along the engagement projection.

14. (Previously Presented) The diathermic snare according to claim 1, wherein the distal-end bending portion is bendable at a substantially right angle with respect to the plane formed by the loop section.

15. (Previously Presented) The diathermic snare according to claim 1, wherein the distal-end bending portion is bendable at an acute angle with respect to the plane formed by the loop section.

16. (Previously Presented) A diathermic snare used in combination with an endoscope, the endoscope including an inserting section which is inserted into a body cavity and which has a distal end and a proximal end, and a cylindrical cap section mounted on the distal end of the inserting section, the cap section having a distal end, a proximal end and an engagement projection having a bending portion that bends inward at the distal end of the cap section,

wherein the diathermic snare comprises:

an elongated flexible sheath having a distal end and a proximal end;

an operating wire inserted into the sheath so as to move forward and backward and having a distal end and a proximal end;

a snare wire coupled to the distal end of the operating wire and having a loop section which expands like a loop;

an operating section coupled to the proximal end of the sheath and including a guide member extending in an axial direction of the sheath and a slider which moves forward and backward in the axial direction of the sheath along the guide member and which is coupled to the proximal end of the operating wire; the loop section of the snare wire projecting from the distal end of the sheath, the snare wire expanding like a loop, and the loop section expanding along an inner circumference of the engagement projection when the slider moves toward along the guide member; and the loop section being stored in the sheath when the slider moves backward along the guide member; and

a bending portion provided at the distal end of the loop section, the bending portion ending in a direction that intersects a plane formed by the loop section and conforming to a corner of the bending portion of the engagement projection when the loop section expands along the inner circumference of the projection;

wherein the cap section has an inclined plane corresponding to a plane of the distal end of the cap section which is inclined to the axial direction of the sheath and the bending portion of the loop section bends in the axial direction of the sheath.

17. (Previously Presented) The medical instrument system according to claim 16, wherein the plane formed by the loop section has an inclination angle that is set such that the plane is almost parallel to the inclined plane of the cap section.

18. (Previously Presented) The medical instrument system according to claim 16, wherein:

the inclined plane of the cap section inclines at an acute angle in the axial direction of the sheath; and

the bending portion of the loop section bends at a bend angle that is equal to an inclination angle of the inclined plane.